





MATERIAL SAFETY DATA SHEET

CAP – PP – MSDS – B19.0GA – 018

PAGE : 1 / 2

PROTECTIVE CLOTHING (PICTOGRAM)	ACUTE HEALTH	FIRE	REACTIVITY	HAZARD RATING
	 0	 1	 0	LEAST = 0 HIGH = 3 SLIGHT = 1 MODERATE = 2 EXTREME = 4

* FOR ACUTE CHRONIC HEALTH EFFECT REFER TO THE DISCUSSION IN SECTION 3

SECTION 1	: SUBSTANCE IDENTITY & COMPANY CONTACT INFORMATION
PRODUCT/MATERIAL	: POLYPROPYLENE IMPACT COPOLYMER RESIN INJECTION GRADE
PRODUCT GRADE	: TRILENE B19.0GA
CHEMICAL MOLECULAR FORMULA	: (C ₃ H ₆) _n
CHEMICAL NAME	: POLYPROPYLENE
CHEMICAL FAMILY	: POLYOLEFIN
MANUFACTURER	: PT. CHANDRA ASRI PETROCHEMICAL TBK (CAP)
ADDRESS	: JL. RAYA ANYER Km.123 - CIWANDAN - CILEGON - WEST JAVA - INDONESIA, 42447
PHONE	: +62 21 530 7950
FAX	: +62 21 530 8930

SECTION 2	: HAZARDS IDENTIFICATION
HAZARDOUS COMPONENTS	: NONE

SECTION 3	: CHEMICAL COMPOSITIONS & DATA ON COMPONENTS			
NO.	COMPOSITION	GRADE: TRILENE B19.0GA	CAS-NUMBER	PERCENT
P	POLYPROPYLENE IMPACT COPOLYMER			100
1	POLYPROPYLENE IMPACT COPOLYMER		69191-21-5	> 99
2	MINOR ADDITIVES			< 1

SECTION 4	: FIRST AID MEASURES
* THE HEALTH EFFECTS BELOW ARE BASED UPON COMPONENT HEALTH EFFECTS CONSISTENT WITH REQUIREMENT UNDER OSHA HAZARD COMMUNICATION (29 CFR 1910.1200)	
EYE CONTACT	: IF MOLTEN MATERIAL CONTACTS THE EYE, FLUSH IMMEDIATELY WITH PLENTY OF WATER. GET MEDICAL ATTENTION IMMEDIATELY IF DISCOMFORT PERSISTS.
SKIN CONTACT	: IF MOLTEN MATERIAL CONTACTS THE SKIN, COOL AS QUICKLY AS POSSIBLE. DO NOT ATTEMPT TO PEEL THE MATERIAL FROM SKIN. GET MEDICAL ATTENTION.
INHALATION	: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST
INGESTION	: MATERIAL IS NOT EXPECTED TO BE ABSORBED FROM THE GASTROINTESTINAL TRACT SO THAT INDUCTION OF VOMITTING SHOULD NOT BE NECESSARY
NOTE TO PHYSICIANS	: BURNS SHOULD BE TREATED AS THERMAL BURNS. THE MATERIAL WILL COME OFF AS HEALING OCCURS; THEREFORE, IMMEDIATE REMOVAL FROM THE SKIN IS NOT NECESSARY. THERE IS NO SPECIFIC ANTIDOTE, TREAT SYMPTOMATICALLY.

SECTION 5	: FIRE-FIGHTING MEASURES
FLASH POINT AND METHOD	: NOT APPLICABLE
FLAMMABLE LIMITS / % VOLUME IN AIR	: NOT APPLICABLE
EXTINGUISHING MEDIA	: USE WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL-TYPE OR UNIVERSAL-TYPE FOAMS APPLIED BY MANUFACTURER'S RECOMMENDED TECHNIQUE
EXTINGUISHING MEDIA	: USE WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL-TYPE OR UNIVERSAL-TYPE FOAMS APPLIED BY MANUFACTURER'S RECOMMENDED TECHNIQUE
FIRE FIGHTING PROCEDURES AND PRECAUTION	: MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.
UNUSUAL FIRE AND EXPLOSION HAZARDS	: TREAT AS A SOLID THAT CAN BURN. MOLDED PARTS GENERALLY BURN SLOWLY WITH A LOW SMOKE DENSITY AND FLAMING DRIPS. UNDER CERTAIN CONDITIONS CAN BURN WITH A HIGH SMOKE DENSITY.

SECTION 6	: ACCIDENTAL RELEASE MEASURES
SMALL SPILL & LEAK	: PELLETS ON THE FLOOR COULD PRESENT A SERIOUS SLIPPING PROBLEM. EXERCISE GOOD HOUSEKEEPING TO AVOID THIS HAZARD. SWEEP, SHOVEL OR VACUUM MATERIAL INTO CLEAN CONTAINERS.
LARGE SPILL & LEAK	: USE A SHOVEL TO PUT THE MATERIAL INTO A CONVENIENT WASTE DISPOSAL CONTAINER. DO NOT ALLOW ANY POTENTIALLY CONTAMINATED WATER WITH PELLETS TO ENTER ANY WATERWAY, SEWER OR DRAIN.

SECTION 7	: HANDLING & STORAGE
PERSONAL PRECAUTIONARY MEASURES	: AVOID CONTACT WITH MOLTEN MATERIAL
HANDLING	: MAINTAIN GOOD HOUSEKEEPING. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME OR ANY IGNITION SOURCE. USE WITH ADEQUATE VENTILATION. AFTER HANDLING, ALWAYS WASH HANDS THOROUGHLY WITH SOAP AND WATER. SPILLED PELLETS MAY CREATE A SLIPPING HAZARD. ELECTROSTATIC CHARGE MAY BUILD UP DURING HANDLING. GROUNDING OF EQUIPMENT IS RECOMMENDED.
STORAGE	: STORE IN A DRY PLACE WITH ADEQUATE VENTILATION AND AWAY FROM DIRECT SUNLIGHT, EXCESSIVE HEAT AND STRONG OXIDIZERS. KEEP PACKAGING (CONTAINER) CLOSED TO PREVENT CONTAMINATION.

SECTION 8	: EXPOSURE CONTROLS & PERSONAL PROTECTION
VENTILATION	: ALTHOUGH GENERAL ROOM VENTILATION SHOULD BE ADEQUATE IN MOST APPLICATIONS, LOCAL EXHAUST VENTILATION IS RECOMMENDED FOR CONTROL OF AIRBORNE DUST, FUMES AND VAPORS, PARTICULARLY IN CONFINED AREAS.
RESPIRATORY PROTECTION	: USE NIOSH APPROVED RESPIRATOR IF UNABLE TO CONTROL AIRBORNE DUST, FUMES AND VAPORS
EYE PROTECTION	: WEAR EYE PROTECTION (SAFETY GLASSES, GOGGLES, FACESHIELDS) WHEN PROCESSING.
SKIN & BODY PROTECTION	: WEAR CHEMICAL-RESISTANT GLOVES, HEAT PROTECTIVE GLOVES AND PROTECTIVE CLOTHING AS WELL AS A FACESHIELD.
OTHER PERSONAL PROTECTION	: USE SAFETY NON-SLIP SHOES IN AREA WHERE SPILLS OR LEAKS OCCUR.

CONTINUED ON NEXT PAGE

CAP – PP – MSDS – B19.0GA – 018		PRODUCT NAME : POLYPROPYLENE IMPACT COPOLYMER RESIN INJECTION GRADE		PAGE : 2 / 2
SECTION 9 : PHYSICAL & CHEMICAL PROPERTIES				
BOILING POINT (°C)	MELT FLOW RATE ^{230/2.16} (g/10min)	SPECIFIC GRAVITY (H ₂ O=1)	VAPOR PRESSURE (mmHg)	
NOT APPLICABLE	9.0	<1	NOT APPLICABLE	
MELTING POINT (°C)	DENSITY (g/cm ³)	SOLUBILITY (IN WATER)	VAPOR DENSITY (AIR = 1)	
160-170	0.900	INSOLUBLE	NOT APPLICABLE	
EVAPORATION RATE (N-BUTYL ACETATE = 1)	: NOT APPLICABLE			
APPEARANCE AND ODOR	: 3mm Ø SOLID, WHITISH IN COLOR AND ESSENTIALLY ODORLESS PELLETT			
FLASH POINT	: NOT APPLICABLE, COMBUSTIBLE SOLID			
SECTION 10 : STABILITY & REACTIVITY				
STABILITY	: STABLE UNDER NORMAL OPERATING CONDITIONS OF STORAGE, HANDLING AND USE.			
HAZARDOUS POLYMERIZATION	: NOT LIKELY TO OCCUR UNDER NORMAL OPERATING CONDITIONS OF STORAGE, HANDLING AND USE.			
CONDITIONS AND MATERIALS TO AVOID	: STRONG OXIDIZING AGENTS,TEMPERATURE OVER 300°C, SPARKS AND OPEN FLAME.			
HAZARDOUS DECOMPOSITION PRODUCTS	: THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT ON THE COMBUSTION CONDITIONS. A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID PARTICULATES AND GASES WILL EVOLVED WHEN THIS MATERIAL UNDERGOES PYROLYSIS OR COMBUSTION. CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION.			
SECTION 11 : TOXICOLOGICAL INFORMATION				
MATERIAL IS CONSIDERED ESSENTIALLY INERT, NON-TOXIC AND PRACTICALLY NOT HARMFUL AS WELL AS NOT HAZARDOUS SUBSTANCES UNDER RoHS REGULATION. EXPOSURES TO HIGH LEVELS OF DUST OR HEATED FUMES MAY CAUSE IRRITATION.				
SECTION 12 : ECOLOGICAL INFORMATION				
ECOTOXICITY	: MATERIAL IS NOT EXPECTED TO BE HARMFUL TO AQUATIC ORGANISMS.			
ENVIRONMENTAL FATE	: MATERIAL IS NOT VOLATILE, INSOLUBLE IN WATER, AND RESISTANT TO BIODEGRADATION.			
SECTION 13 : DISPOSAL CONSIDERATIONS				
WASTE DISPOSAL	: PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.			
SECTION 14 : TRANSPORT INFORMATION				
TRANSPORTATION CLASSIFICATION	: NOT CONTROLLED UNDER DOT (UNITED STATES), TDG (CANADA), ADR (EUROPE), IMDG, AND IATA.			
SECTION 15 : REGULATIONS				
THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES.				
SECTION 16 : OTHER INFORMATION				
ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:				
ACGIH : AMERICAN CONFERENCE of GOVERNMENTAL INDUSTRIAL HYGIENISTS				
DOT : DEPARTMENT OF TRANSPORTATION				
NIOSH : NATIONAL INSTITUTE for OCCUPATIONAL SAFETY & HEALTH				
OSHA : OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION				
RoHS : RESTRICTION of HAZARDOUS SUBSTANCES				
THE INFORMATION EXPRESSED HEREIN ARE THOSE OF QUALIFIED CURRENT KNOWLEDGE AND EXPERIENCE ANT THAT THE INFORMATION IS SUFFICIENT OF ALL CASES. USERS SHOULD CONSIDER THE DATA AS A SUPPLEMENT TO OTHER INFORMATION AND SHOULD MAKE INDEPENDENT DETERMINATION OF ITS SUITABILITY, THEIR EMPLOYEES AND CUSTOMERS, AND OF THE ENVIRONMENTAL PROTECTION TO ASSURE PROPER USE AND DISPOSAL OF THE MATERIAL. RESPONSIBILITY FOR USAGE, STORAGE, HANDLING AND DISPOSAL OF THE PRODUCTS DESCRIBED HEREIN, WHETHER ALONE, OR IN COMBINATION WITH ANY OTHER SUBSTANCE, IS THAT OF THE PURCHASER AND/OR END-USER. CAP MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF. CAP ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.				
FOR ADDITIONAL INFORMATION, PLEASE EMAIL : TSPD@capcx.com				Issued Date: 03/02/2011